

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

PRODUCT DATA SHEET

MAGNUM ENGINE OIL SF/CF 30

PRODUCT DESCRIPTION

Magnum Engine Oil SF/CF 30 is a mixed fleet engine oil designed to meet the requirements of passenger car and light truck gasoline and diesel engines where API SF and CF performance is required.

APPLICATION

- Naturally Aspirated and Turbocharged Diesel Engines
- Gasoline Engines
- Off-highway equipment and stationary engines
- 2-stroke Detroit Diesel Engines

BENEFITS

- Excellent protection against wear and corrosion.
- Outstanding control of high temperature deposits.
- Good control of low temperature sludge and deposit

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

TYPICAL PROPERTIES

Property	Test Method	Typical value
Density at 20°C,kg/l	ASTM D1298	0.876
Viscosity @ 100°C,cSt	ASTM D445	11.0
Viscosity @ 40°C,cSt	ASTM D445	95
Viscosity Index	ASTM D2270	100
Pour point °C	ASTM D97	-21
Flash point °C	ASTM D92	212
Total Base Number mgKOH/g	ASTM D2896	6.2

SPECIFICATIONS

- API SF/CF

This data sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY