

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

PRODUCT DATA SHEET

MAGNUM PRO 504 SAE 5W-30

PRODUCT DESCRIPTION

Magnum PRO 504 SAE 5W-30 is a fully synthetic passenger car motor oil suitable for modern turbocharged and naturally aspirated petrol and diesel engines. Based on the latest Mid SAPS additive technology and high viscosity index hydro-processed base oils, Magnum PRO 504 SAE 5W-30 is approved for use where an ACEA C3 lubricant is recommended.

APPLICATION

- Suitable for a large number of Volkswagen and Audi gasoline and diesel passenger cars or light duty diesel vans with or without a turbocharger, and is mandatory for VW/Audi diesel engines with DPF.
- Magnum PRO SAE 5W-30 is recommended for vehicles requiring a VW 504 00/507 00 approved engine oil

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

BENEFITS

- Viscosity grade SAE 5W-30 minimizes lubricant hydrodynamic friction, and allows fuel economy benefits especially when the oil is cold.
- Improved oil flow at start up, hence reaching operating temperature faster.
- Provides better engine response and driving comfort.
- Mid SAPS additive system ensures Good Thermal and Oxidation stability hence reducing oil thickening
- Environmentally friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

PERFORMANCE LEVEL(Meets the requirements of):

- ACEA C3
- **VW 504.00/507.00**
- PORCHE C30
- BMW LL-04
- MB 229.52/51/31

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

TYPICAL PROPERTIES:

Property	Test Method	Typical Data
Density 20 °C, kg/l	ASTM D1298	0,85
Viscosity 40 °C, cSt	ASTM D445	65.1
Viscosity 100 °C, cSt	ASTM D445	11.8
Viscosity Index	ASTM D2270	179
Pour Point, °C	ASTM D97	-45
Flash Point, °C	ASTM D93	> 210
CCS @ -30°C, cP	ASTM D5293	5950
Total Base Number, mgKOH/g	ASTM D2896	8.5
Sulphated Ash,%m/m	ASTM D874	0.78

STORAGE

All packages should be stored under cover. If stored outside drums should be laid horizontally to avoid water ingress and damage to markings on the drums. Products should not be stored above 60°C or exposed to hot sun or freezing conditions.

This data sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY