

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

PRODUCT DATA SHEET

MAGNUM PRO 913 SAE 5W-30

PRODUCT DESCRIPTION

MAGNUM PRO 913 SAE 5W-30 is a premium quality ,full synthetic high performance lubricant based on Full SAPS (Sulphated Ash, Phosphorous, Sulfur) Additive Technology. Suitable for all types of Gasoline and Diesel engines requiring a Fuel Economy lubricant (ACEA A5/B5 standard) in an SAE 5W-30 viscosity grade.

APPLICATION

- FORD M2C 913-D specification covers many Diesel and Gasoline engines currently requiring specifications FORD WSS M2C 913-A, 913-B and 913-C.
- VW Amarok Engines requiring a lubricant that meets WSS M2C 913C or 913D specifications
- Compatible with exhaust gas after treatment devices such as catalytic converters and Diesel Particulates Filter (DPF).

BENEFITS

- Viscosity grade SAE 5W-30 minimizes lubricant hydrodynamic friction, and allows fuel economy benefits especially when the oil is cold.
- Improved oil flow at start up, hence reaching operating temperature faster.
- Good Thermal and Oxidation stability hence reducing oil thickening from soot formation
- Environmentally friendly, this type of oil allows fuel consumption reduction and therefore minimizes greenhouse gases (CO₂) emissions.

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

PERFORMANCE LEVEL(Meets the requirements of):

- API SL
- ACEA A5/B5
- Renault RN0700
- **FORD M2C913D**
- STJLR 03.5003

TYPICAL PROPERTIES:

Property	Test Method	Typical Data
Density 20 °C, kg/l	ASTM D1298	0,857
Viscosity 40 °C, cSt	ASTM D445	58.5
Viscosity 100 °C, cSt	ASTM D445	10.5
Viscosity Index	ASTM D2270	170
Pour Point, °C	ASTM D97	-45
Flash Point, °C	ASTM D93	> 200
CCS @ -30°C, cP	ASTM D5293	5250
Sulphated Ash,%m/m	ASTM D874	1.07

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

STORAGE

All packages should be stored under cover. If stored outside drums should be laid horizontally to avoid water ingress and damage to markings on the drums. Products should not be stored above 60°C or exposed to hot sun or freezing conditions.

This data sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY