

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

PRODUCT DATA SHEET

MAGNUM ENGINE OIL SN/CF 10W-40

PRODUCT DESCRIPTION

MAGNUM ENGINE OIL SN/CF 10W-40 is a high performance oil suitable for modern turbocharged petrol engines formulated with hydrotreated base stocks and latest conventional SAPS additive technology.

APPLICATION AND BENEFITS

- Suitable for all types of petrol engines including high performance turbocharged passenger cars.
- Suitable for passenger car diesel engines and light commercial vehicles
- Provides excellent deposits and sludge control
- Resists oxidation

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY

**MAGNUM
OIL**

All round Engineering

Tel: 011 024 8888



Reg no.2012/117416/07

Vat no.4140261209

Email: larry@oil4africa.co.za

41 Illana Street Delville, Germiston

TYPICAL PROPERTIES

Property	Test Method	Typical value
Density at 20°C ,g/ml	ASTM D1298	0.883
Viscosity @ 100°C ,cSt	ASTM D445	14.8
Viscosity @ 40°C ,cSt	ASTM D445	98.5
Viscosity Index	ASTM D2270	146
Pour point, °C	ASTM D97	-33
Flash point, °C	ASTM D92	226

SPECIFICATIONS

- API SN/CF
- ACEA A3/B4
- MB229.1/226.5
- VW 502.00/505.00
- RN 710/700
- PSAB71-2300

This data sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product.

Directors: Larry Rajpal & Saitish Rajpal

NATIONALLY